

SOLID STATE AREA LIGHTING

8530 SERIES-LED

SPECIFICATIONS

HOUSING

Heavy wall cast aluminum (A356 alloy; < 0.2% copper) construction. Powder coated for use in concrete. Two (2) 3/4" NPT conduit entries provided at bottom of Splice Compartment.

LENS FRAME

Cast aluminum (A356 alloy; < 0.2% copper) construction in louvered frame or open frame configurations.

LENS

LOUVERED LENS FRAME: 3/16" tempered glass, frosted (ALF) or prismatic (ALP).

OPEN LENS FRAME: 3/16" tempered glass, frosted (NLF) or prismatic (NLP).

LED EMITTERS

High Output LED's are driven at 350mA for nominal 1 Watt output each. LED's are available in standard Neutral White (4000K), or optional Cool White (5000K) or Warm White (3000K). Consult Factory for other LED options.

LED DRIVER


Constant current LED drivers are UL and cUL recognized mounted on a single plate and factory prewired with quick-disconnect plugs. Drivers are electronic and have a power factor of >.90 and a minimum operating temperature of -40°F. Drivers accept an input of 120-277V, 50/60Hz. (Consult factory for dimming applications.)

FINISH

Polyester powder coat incorporates four step iron phosphate process to pretreat metal surface for maximum adhesion. Top coat is baked at 400°F for maximum hardness and exterior durability.


PROJECT NAME: _____

PROJECT TYPE: _____



8530-AL

PATENT PENDING





8530-NL

PATENT PENDING


8530 SERIES - LED

S P E C I F I C A T I O N S


OPTICAL CONFIGURATIONS




LED POWER ARRAY™ MODULES



8530-AL-LED
Louvered Face
12 LED







8530-NL-LED
Open Face
12 LED



LED MODULE

Spec/Order Example: 8530-NLP/12LED-NW/120/RAL-7004-S

S P E C / O R D E R I N G I N F O R M A T I O N

MODEL	# of LED's	COLOR TEMP - CCT	VOLTAGE	FINISH	OPTIONS
MODEL	LED	FINISH	OPTIONS		
<input type="checkbox"/> 8530 - ALF  Louvered Face Frosted Glass	<input type="checkbox"/> 12LED (14 Watts)	<input type="checkbox"/> NW (4000K)* *STANDARD <input type="checkbox"/> CW (5000K) <input type="checkbox"/> WW (3000K) OTHER LED COLORS AVAILABLE CONSULT FACTORY 1 - CONSULT FACTORY FOR 347V APPLICATION	<input type="checkbox"/> 120 <input type="checkbox"/> 208 <input type="checkbox"/> 240 <input type="checkbox"/> 277	STANDARD TEXTURED FINISH <input type="checkbox"/> BLACK..... RAL-9005-T <input type="checkbox"/> WHITE..... RAL-9003-T <input type="checkbox"/> GREY..... RAL-7004-T <input type="checkbox"/> DARK BRONZE.... RAL-8019-T <input type="checkbox"/> GREEN..... RAL-6005-T FOR SMOOTH FINISH REPLACE SUFFIX "-T" WITH SUFFIX "-S" (EXAMPLE: RAL-9005-S) CONSULT FACTORY FOR CUSTOM COLORS	<input type="checkbox"/> 10KV SURGE PROTECTOR..... 10SP <input type="checkbox"/> SINGLE FUSED (120V., 277V)..... SF <input type="checkbox"/> DOUBLE FUSE (208V., 240V)..... DF
<input type="checkbox"/> 8530 - ALP  Louvered face Prismatic Glass					
<input type="checkbox"/> 8530 - NLF  Open Face Frosted Glass					
<input type="checkbox"/> 8530 - NLP  Open Face Prismatic Glass					