

# SOLID STATE AREA LIGHTING

## LAFC SERIES-LED SPECIFICATIONS

### LUMINAIRE

One piece high impact polycarbonate patterned diffusing globe provided with durable corrosion resistant cast aluminum fitter and ring. Standard fitter has 3" I.D. opening for tenon. All hardware is stainless steel.

### LED POWER ARRAY™

Three-dimensional array of individual LED Tubes fastened to a retaining plate. Each LED Tube consists of circuit board populated with a multiple of LED's and is mechanically fastened to a radial aluminum heat sink. An acrylic Lens and end cap protects the LED Tube's internal components.

**ANGLED POWER ARRAY™:** Micro-Reflectors mounted around each LED control the raw light output. LED Tubes are uniquely aimed horizontally and vertically and combined to produce highly efficient IES Distribution Types II, III, IV and V. Used in conjunction with a clear patterned diffusing globe.

**VERTICAL POWER ARRAY™ WITH GLASS REFRACTOR:** LED Tubes are aligned vertically and arranged radially to produce an even raw light distribution that simulates standard light sources. Array is secured within a 6" Prismatic Glass Refractor which provides the optical control. Used in conjunction with a clear patterned diffusing globe.

**VERTICAL POWER ARRAY™:** LED Tubes are aligned vertically and arranged radially to produce an even raw light distribution that simulates standard light sources. Produces a minimal glare, symmetric diffuse light distribution. Used in conjunction with an opal patterned diffusing globe.

### LED EMITTERS

High Output LED's are driven at 350mA for nominal 1 Watt output each. LED's are available in standard Neutral White (4000K), or optional Cool White (5000K) or Warm White (3000K). Consult Factory for other LED options.

### LED DRIVER

UL and CUL recognized High Power Factor, Constant Current LED drivers operate on input voltages from 120-277VAC, 50/60hz. Consult Factory for 347-480VAC. Driver is mechanically fastened to a retaining bracket. Main power quick disconnect provided. Driver has a minimum 4KV of internal surge protection, 10KV & 20KV Surge Protector optional. Dimming and High-Low Driver options available.

### FINISH

Polyester powder coat incorporates four step iron phosphate process to pretreat metal surface for maximum adhesion. Top coat is baked at 400°F for maximum hardness and exterior durability.

PROJECT NAME: \_\_\_\_\_



PROJECT TYPE: \_\_\_\_\_



**LAFC**

\* SHOWN WITH STANDARD -YA FITTER

PATENT PENDING



FIXTURE	A	B
LAFC1*	18.5" 470mm	32" 813mm
LAFC2*	17" 432mm	28" 711mm




2015028

# LAFC SERIES - LED

## S P E C I F I C A T I O N S


### OPTIONAL FITTERS



LAFC1-YB




LAFC2-YB



LAFC1-YD\*




LAFC2-YD\*



LAFC1-YE\*



LAFC2-YE\*



LAFC1-YG



LAFC2-YC

### LED POWER ARRAY™ MODULES



**LAFC1 - LED** E.P.A.= 1.67

#### ANGLED ARRAY

Available in:  
10 Array 80 LED Max.

#### GLASS REFRACTOR w/ VERTICAL ARRAY

Available in:  
6 Array 36 LED Max.

#### VERTICAL ARRAY

Available in:  
6 Array 48 LED Max.  
8 Array 64 LED Max.  
10 Array 80 LED Max.



**LAFC2 - LED** E.P.A.= 1.23

#### ANGLED ARRAY


Available in:  
8 Array 48 LED Max.

#### GLASS REFRACTOR w/ VERTICAL ARRAY

Available in:  
6 Array 36 LED Max.

#### VERTICAL ARRAY


Available in:  
6 Array 48 LED Max.  
8 Array 64 LED Max.



**APA - Angled Array**  
Base mount



**GRV - Glass Refractor**  
w/ Vertical Array  
Base mount



**VPA - Vertical Array**  
Base mount

(Specifications subject to  
change without prior notice.)

BRASS  
FINIAL

ORNAMENTAL  
FINIAL

\* AVAILABLE WITH MINI BUTTON PHOTOCELLS  
SEE OPTIONS

Spec/Order Example: LAFC1-APA-IV/60LEDCW/1/RAL-7004-T/WP

## O R D E R I N G I N F O R M A T I O N

LUMINAIRE-FITTER	OPTICS	# of LED's	COLOR	VOLTAGE	MOUNTING	FINISH	OPTIONS
LUMINAIRE	OPTICS	LED			MOUNTING	FINISH	OPTIONS
<b>LUMINAIRE-FITTER</b>	<b>ANGLED POWER ARRAY</b> (CLEAR PATTERNED LENS)	<b>No. LEDs</b>	<b>COLOR</b>		<b>ARM MOUNT</b>	<b>STANDARD TEXTURED FINISH</b>	<b>LENS OPTIONS:</b>
<input type="checkbox"/> LAFC1-LED-YA	<input type="checkbox"/> APA - II	<input type="checkbox"/> <b>80LED</b> (89 Watts)	<input type="checkbox"/> <b>48LED</b> (53 Watts)	<input type="checkbox"/> <b>NW (4000K)*</b> *STANDARD	<input type="checkbox"/> 1	<input type="checkbox"/> <b>BLACK</b> <b>RAL-9005-T</b>	<input type="checkbox"/> CLEAR PATTERNED POLYCARBONATE ... <b>CP</b>
<input type="checkbox"/> LAFC1-LED-YB	<input type="checkbox"/> APA - III	<input type="checkbox"/> <b>60LED</b> (67 Watts)	<input type="checkbox"/> <b>32LED</b> (36 Watts)	<input type="checkbox"/> <b>CW (5000K)</b>	<input type="checkbox"/> 2-180	<input type="checkbox"/> <b>WHITE</b> <b>RAL-9003-T</b>	<input type="checkbox"/> OPAL PATTERNED POLYCARBONATE ... <b>WP</b>
<input type="checkbox"/> LAFC1-LED-YD	<input type="checkbox"/> APA - IV	<input type="checkbox"/> <b>40LED</b> (45 Watts)		<input type="checkbox"/> <b>WW (3000K)</b>	<input type="checkbox"/> 2-90	<input type="checkbox"/> <b>GREY</b> <b>RAL-7004-T</b>	<input type="checkbox"/> CLEAR PATTERNED ACRYLIC ... <b>CA</b>
<input type="checkbox"/> LAFC1-LED-YE	<input type="checkbox"/> APA - V	Wattages are Max Input Watts		<b>OTHER LED COLORS</b> AVAILABLE CONSULT FACTORY	<input type="checkbox"/> 3-90	<input type="checkbox"/> <b>DARK BRONZE</b> <b>RAL-8019-T</b>	<input type="checkbox"/> BRASS FINIAL ... <b>BF</b>
<input type="checkbox"/> LAFC1-LED-YG				<b>VOLTAGE</b>	<input type="checkbox"/> 3-120	<input type="checkbox"/> <b>GREEN</b> <b>RAL-6005-T</b>	<input type="checkbox"/> ORNAMENTAL FINIAL ... <b>OF</b>
<input type="checkbox"/> LAFC2-LED-YA	<b>GLASS REFRACTOR</b> (CLEAR PATTERNED LENS)	<input type="checkbox"/> <b>36LED</b> (41 Watts)	<input type="checkbox"/> <b>36LED</b> (41 Watts)	<input type="checkbox"/> 120	<input type="checkbox"/> 4-90		<input type="checkbox"/> HOUSE SIDE SHIELD ... <b>HS</b>
<input type="checkbox"/> LAFC2-LED-YB	<input type="checkbox"/> GRV - III			<input type="checkbox"/> 208	<input type="checkbox"/> 3-120		<input type="checkbox"/> DIMMABLE DRIVER(S) (0-10V) ... <b>DIM</b>
<input type="checkbox"/> LAFC2-LED-YD	<input type="checkbox"/> GRV - V			<input type="checkbox"/> 240	<input type="checkbox"/> 4-90		<input type="checkbox"/> HIGH-LOW DIMMING FOR HARDWIRED SWITCHING OR NON-INTEGRATED MOTION SENSOR ... <b>HLWS</b>
<input type="checkbox"/> LAFC2-LED-YE				<input type="checkbox"/> 277	<b>WALL MOUNT</b>		<input type="checkbox"/> PHOTO CELL + VOLTAGE (EXAMPLE: PC120V) ... <b>PC+V</b>
<input type="checkbox"/> LAFC2-LED-YC	<b>VERTICAL POWER ARRAY</b> (OPAL LENS)	<input type="checkbox"/> <b>80LED</b> (89 Watts)	<input type="checkbox"/> <b>64LED</b> (72 Watts)	<input type="checkbox"/> 347	<input type="checkbox"/> WM		<input type="checkbox"/> 10KV SURGE PROTECTOR ... <b>10SP</b>
	<input type="checkbox"/> VPA - SYM	<input type="checkbox"/> <b>64LED</b> (72 Watts)	<input type="checkbox"/> <b>48LED</b> (53 Watts)	<input type="checkbox"/> 480	<b>POST TOP</b>		<input type="checkbox"/> 20KV SURGE PROTECTOR (277V & 480V Only) ... <b>20SP</b>
		<input type="checkbox"/> <b>48LED</b> (53 Watts)	<input type="checkbox"/> <b>36LED</b> (41 Watts)		<input type="checkbox"/> PT		
		Wattages are Max Input Watts					